



International Energy Services



RIG # 18

IDECO H-725



GENERAL PARTICULARS

Depth rating: 10,000 ft
 Horsepower: 750 HP
 Max. Hookload: 358,000 lbs

DRAWWORKS

Ideco
 Type: H-725D
 HP rating: 750 HP
 Drilling line: 11/8 EIPS
 Auxiliary brake: V-80 Parmac
 Hydromatic
 Drive type: Cat 3406C DITA (x2)
 HP rating: 440 HP (x2)

MAST

Ideco
 Type: KM 117-358-AH Kwik
 Lift
 Height: 117 ft
 G.N.C.: 429,600 lbs
 Max. hookload: 358,000 lbs

SUBSTRUCTURE

Ideco
 Type: Telescoping
 Height: 16ft
 Casing load: 320,000 lbs
 Setback load: 200,000 lbs

TOP DRIVE

Nil
 Type:
 Rating:
 Torque:
 reckon

ROTARY TABLE

Ideco
 Type: LR-275-K
 Table opening: 27 1/2"

POWER GENERATION

Cat. SR 4 (x2)
 Gen type: 320 kW (x2)
 Gen rating: Cat 3406C DITA (x2)
 Engine type: 475 HP (x2)
 HP rating:

MUD PUMPS

Emsco
 Type: F-800 (x2)
 HP rating: 800 HP

SCR

Nil
 Type:

MUD SYSTEM

Active system capacity: 680 bbls
 Reserve system capacity: Nil

BOP'S

Shaffer 11" 5,000 psi
 Annular: Shaffer 11" 5,000
 BOP's: Double Gate

Pressure rating: 5,000 psi