



# International Energy Services



**RIG # 18**

**IDECO H-725**



**GENERAL PARTICULARS**

Depth rating:	10,000 ft
Horsepower:	750 HP
Max. Hookload:	358,000 lbs

**DRAWWORKS**

Type:	Ideco H-725D
HP rating:	750 HP
Drilling line:	1 1/8 EIPS
Auxiliary brake:	V-80 Parmac Hydromatic
Drive type:	Cat 3406C DITA (x2)
HP rating:	440 HP (x2)

**SUBSTRUCTURE**

Type:	Ideco Telescoping
Height:	16ft
Casing load:	320,000 lbs
Setback load:	200,000 lbs

**ROTARY TABLE**

Type:	Ideco LR-275-K
Table opening:	27 1/2"

**MUD PUMPS**

Type:	Emsco F-800 (x2)
HP rating:	800 HP

**MUD SYSTEM**

Active system capacity:	680 bbls
Reserve system capacity:	Nil
Shale shakers:	DFE SCR1 (x2)
Pressure rating:	5,000 psi

**MAST**

Type:	Ideco KM 117-358-AH Kwik Lift
Height:	117 ft
G.N.C.:	429,600 lbs
Max. hookload:	358,000 lbs

**TOP DRIVE**

Type:	Nil
Rating:	
Torque:	
reckon	

**POWER GENERATION**

Gen type:	Cat. SR 4 (x2)
Gen rating:	320 kW (x2)
Engine type:	Cat 3406C DITA (x2)
HP rating:	475 HP (x2)

**SCR**

Type:	Nil
-------	-----

**BOP'S**

Annular:	Shaffer 11" 5,000 psi
BOP's:	Shaffer 11" 5,000 Double Gate