

**RIG # 19****KREMCO K-600-H****GENERAL PARTICULARS**

Depth rating: 8,500 ft
 Horsepower: 600 HP
 Max. Hookload: 300,000 lbs

DRAWWORKS

Kremco
 Type: K-600-H
 HP rating: 600 HP
 Drilling line: 1 1/8" EIPS,
 Auxiliary brake: 22" Hydromatic
 Drive type: Cat 3406B TA (x2)
 HP rating: 400 HP (x2)

MAST

Kremco
 Type: Hydraulic Raise and
 Telescoping
 Height: 112 ft
 G.N.C.: 325,000 lbs
 Max. hookload: 300,000 lbs

SUBSTRUCTURE

Kremco
 Type: Telescoping
 Height: 17 ft
 Casing load: 270,000 lbs
 Setback load: 200,000 lbs

TOP DRIVE

Optional
 Type: Tesco HMI
 Rating: 250 ton 475 HP
 Torque: 21,000 ft lbs

ROTARY TABLE

Ideco
 Type: SR-175
 Table opening: 23"

POWER GENERATION

Cat.SR-4 (x2)
 Gen type: 250 kW (x2)
 Gen rating: Cat 3406B TA (x2)
 Engine type: 365 HP (x2)
 HP rating:

MUD PUMPS

National
 Type: 8-P-80 (x2)
 HP rating: 800 HP
 Pressure rating: 5,000 psi

SCR

Nil

MUD SYSTEM

757 bbls
 Active system capacity:
 Shale shakers: DFE SCR1 (x2)
 Pressure rating: 5,000 psi

BOP'S

Shaffer 13.5/8" 5000
 Annular: psi
 BOP's: Shaffer LWS 13.5/8"
 5000 Double Gate