



International Energy Services



RIG # 20

KREMCO K-600-H



GENERAL PARTICULARS

Depth rating:	7,500 ft
Horsepower:	600 HP
Max. Hookload:	270,000 lbs

DRAWWORKS

Type:	Kremco
HP rating:	K-600H
Drilling line:	600 HP
Auxiliary brake:	1-1/8" EIPS
Drive type:	22" Hydromatic
HP rating:	Cat 3406B TA (x2)
	400 HP (x2)

SUBSTRUCTURE

Type:	Kremco
Height:	Telescopic
Casing load:	13 ft
Setback load:	270,000 lbs
	200,000 lbs

ROTARY TABLE

Type:	Ideco
Table opening:	SR-175
	17.1/2"

MUD PUMPS

Type:	Ideco
HP rating:	T-500 (x2)
	500 HP (x2)

MUD SYSTEM

Active system capacity:	594 bbls
Reserve system capacity:	Nil
Shale shakers:	DFE SCR1 (x2)
Pressure rating:	5,000 psi

SPECIAL FEATURES

Highly Mobile

MAST

Type:	Kremco
Height:	Hydraulic Raise and Telescoping
G.N.C.:	109 ft
Max. hookload:	337,500 lbs
	270,000 lbs

TOP DRIVE

Type:	Nil
Rating:	
Torque:	

POWER GENERATION

Gen type:	Cat SR 4 (x2)
Gen rating:	275 kW (x2)
Engine type:	Cat 3408 (x2)
HP rating:	400 HP (x2)

SCR

Type:	Nil
-------	-----

BOP'S

Annular:	Shaffer 11" 5,000
	Annular
BOP's:	Shaffer 11" 5,000
	Double Gate