



International Energy Services



RIG # 26

DRECO 800E-SCR



GENERAL PARTICULARS

Depth rating:	10,000 ft
Horsepower:	800 HP
Max. Hookload:	380,000 lbs
Year of construction/total refurbishment:	1989
Total no. of loads:	Dependant on configuration

DRAWWORKS

Type:	Dreco
HP rating:	800 E
Single line pull:	800 HP
Drilling line:	130,000 lbs
Auxiliary brake:	1 1/8" EIPS
Drive type:	Dretech 7RD 150
HP rating:	EMD-D79
	800 HP

MAST

Type:	Dreco
Height:	Telescoping
G.N.C.:	108 ft
Max. hookload:	532,000 lbs
	380,000 lbs

SUBSTRUCTURE

Type:	Dreco
Height:	Single Piece
Casing load:	20 ft
Setback load:	380,000 lbs
	230,000 lbs

TOP DRIVE

Type:	Nil
Rating:	
Torque:	

ROTARY TABLE

Type:	Oilwell
Table opening:	B 27 1/2
Drive:	27.1/2"
	Independent DC

POWER GENERATION

Gen type:	Brown Boveri
Gen rating:	800 kW (x4)
Engine type:	Cat D398 TAC (x4)
HP rating:	912HP (x4)

MUD PUMPS

Type:	Emsco
HP rating:	F-1000 (x2)
Drive:	1,000 HP (x2)
	EMD - D79

SCR

Type:	IPS
	2,000 SCR

MUD SYSTEM

Active system capacity:	742 bbls
Reserve system capacity:	442 bbls
Shale shakers:	Derrick Flo-Line (x2)
Pressure rating:	5,000 psi

BOP'S

Annular:	Hydril 13.5/8" 5,000
	Annular
BOP's:	2 - CIW 13.5/8"
	Single Gate
	(1-Shear Ram)

SPECIAL FEATURES

Highly mobile