



International Energy Services



RIG # 29

KREMCO K750T



GENERAL PARTICULARS

Depth rating:	9,000 ft
Horsepower:	750 HP
Max. Hookload:	330,000 lbs
Year of construction/total refurbishment:	1995
Total no. of loads:	30

DRAWWORKS

Type:	Kremco
HP rating:	K-750T
Single line pull:	750 HP
Drilling line:	130,000 lbs
Auxiliary brake:	1-1/8" EIPS
Drive Type:	Tri-Services 22" Single hydromatic
HP Rating:	Cat 3406 PCTA (x2)
	350 HP (x2)

MAST

Type:	Kremco
	Hydraulic Raise and Telescoping
Height:	112 ft
G.N.C.:	350,000 lbs
Max. hookload:	330,000 lbs

SUBSTRUCTURE

Type:	Kremco
	Parallelogram Style
Height:	18"
Casing load:	350,000 lbs
Setback load:	280,000 lbs

TOP DRIVE

Type:	Nil
Rating:	
Torque:	

ROTARY TABLE

Type:	Gardner Denver
Table opening:	RT 17 1/2
	17.1/2"

POWER GENERATION

Gen type:	EM Bemac II (x2)
Gen rating:	300 kW (x2)
Engine type:	Cat D353 TAC (x2)
HP rating:	430 HP (x2)

MUD PUMPS

Type:	Oilwell
HP rating:	A600PT (x2)
Drive:	600 HP (x2)
	Cat D379 TAC

SCR

Type:	N/A
-------	-----

MUD SYSTEM

Active system capacity:	997 bbls
Reserve system capacity:	Nil
Shale shakers:	DFE SCR1 (x2)
Pressure rating:	5,000 psi

BOP'S

Annular:	Hydril 11" 3,000
BOP's:	2 - Shaffer SL
	Single Rams 11"
	5M.

SPECIAL FEATURES

Highly mobile