



## RIG # 50

## ENSIGN ADR 100



### GENERAL PARTICULARS

Depth rating:	1300 m (4" DP)
Horsepower:	599 HP
Max. Hookload:	100,000 lbs
Upgraded:	2007

### HOISTING UNIT

Type:	ADR 100
Drive Type	LP Hydraulic
Power source	Detroit Diesel Series 60
HP Rating	599 HP

### MAST

Type:	Ensign ADR
Height:	23.1m (75ft 9")
Static hookload	100,000lbs
Max. torque rating:	27,000 Nm

### SUBSTRUCTURE

Type:	Tandem Axle
Height:	4.3m (14ft 1" )
Rotary Capacity:	N/A
Clear Working Height:	3.3m (10ft 10")

### TOP DRIVE

Type:	Hagglunds CA-50 driven
Rating:	0 – 280 RPM
Torque:	12,900 ft-lb @ 5,000 psi

### ROTARY BUSHING

Rating:	200,000 lbs
Opening:	17 ½ "

### LIGHT PLANT POWER GENERATION

Gen Type:	Detroit Diesel or equivalent
Gen Rating:	224 kW
Engine Type:	Series 50
HP rating:	300 HP

### MUD PUMPS

Type:	Triplex TSM
HP rating:	750HP (x1)
Drive	Detroit Diesel 12V 2,000 or Detroit Series 60

### SCR

Type:	N/A
-------	-----

### MUD SYSTEM

Active system capacity:	220 Bbl (35m <sup>3</sup> )
Shale shakers:	1 x Swaco Mongoose Elliptical motion

### BOP'S

Annular:	9" 3K Annular
BOP's:	9" 3K Double (1 pipe & 1 blind ram) or 9" 3K Single (X2)

### SPECIAL FEATURES

Ensign Pipe Arm & Iron Roughneck Highly Mobile
--